

PRODUCT DATA SHEET

Sackora Lumber Wrap — 9 ft × 2,230 ft

HEAVY-DUTY PE-COATED PP WOVEN WRAP · TWO-TONE WHITE / BLACK

ROLL LENGTH 2,230 ft 680 m	ROLL WIDTH 9 ft 2.74 m	COVERAGE 20,070 ft² 1,864 m ² per roll	FABRIC WEIGHT 85 g/m² PE coated both sides
--	--	--	---

PRODUCT DESCRIPTION

Sackora Lumber Wrap is a heavy-duty woven polypropylene fabric, polyethylene-coated on both sides, engineered to protect lumber, dimensional wood products, and palletized goods through outdoor storage and long-haul export. The flat-tape circular-loom construction delivers tear resistance and dimensional stability across full roll widths.

The two-tone format — white exterior, black interior — reflects solar load on the outside while preventing light bleed-through to wrapped product. Each roll covers over 20,000 square feet, optimized for sawmill, lumber-yard, and exporter throughput.

KEY FEATURES

- 20,070 ft² coverage per roll
- PE coating both sides — fully waterproof
- Tear-resistant flat-tape woven PP
- Two-tone white / black — solar reflective
- UV-stabilized for outdoor service
- 3 in paper core — standard unwinder
- Virgin PP resin
- Fully recyclable

WHERE TO USE

Sawmills & Lumber Yards	Wood Exporters	Pallet & Bundle Covers	Construction Site Material Protection	Outdoor Wood Storage
Pre-Cut Lumber Bundling	Engineered Wood Products	Long-Haul Ocean Export		

TECHNICAL SPECIFICATIONS

Roll Dimensions	9 ft × 2,230 ft · 2.74 m × 680 m
Coverage per Roll	20,070 ft ² · 1,864 m ²
Roll Weight	~152 kg (335 lb)
Construction	Flat-tape circular-loom woven polypropylene
Fabric Weight	85 g/m ² (2.5 oz/yd ²)
Coating	Polyethylene coating, both sides — fully waterproof
Color	White exterior · Black interior
Core	3 in (76 mm) paper core — fits standard unwinding equipment
UV Stabilization	HALS additive package — engineered for outdoor staging
Resin	Virgin polypropylene — no recycled content
Print	Plain — custom print available on request
Pallet Pack	Multiple rolls per pallet — specify on order

HANDLING & APPLICATION
APPLICATION

Mount roll on a standard 3 in spindle unwinder or manual stand. Pull fabric over the wood stack with the white surface facing outward, allowing 6–12 in overhang on each end. Secure with steel strapping, polyester cord, or pressure-sensitive seam tape.

SEALING

Overlap seams a minimum of 6 in. For long-haul export or extended outdoor exposure, seal seams with weather-resistant adhesive tape to prevent water ingress at joints.

STORAGE

Store rolls indoors or under cover, lying horizontally on the wrapper packaging or vertically on the core ends. Avoid stacking heavy items directly on the core to prevent compression and out-of-round deformation.

DISPOSAL & RECYCLING

Manufactured from 100% virgin polypropylene with PE coating — both fully recyclable through standard PP/PE recycling streams. Free of heavy metals and PVC.

PRODUCT DATA SHEET

Sackora Lumber Wrap · 9 ft × 2,230 ft · May 2026, Version 01.00

WWW.SACKORA.COM

 1 (855) 527-7225 · romanfain@sackora.com